

(1) Type Examination Certificate

- (2) No. of the Type Examination Certificate: **ZP/B031/23**
- (3) Product: **Fixed installed stepped ladder**
Type: **ABS Treppenleiter**
- (4) Manufacturer: **ABS Safety GmbH**
- (5) Address: **Gewebering 3, 47623 Kevelaer, Germany**
- (6) The design of this product and any acceptable variation thereto are specified in the schedule to this Type Examination Certificate.
- (7) The certification body of DEKRA Testing and Certification GmbH certifies that this product complies with the fundamental requirements of the standard listed under item 8 below. The examination and test results are set out in the report PB 23-014.
- (8) The requirements of the standard are assured by compliance with
DIN EN ISO 14122-3:2016
- (9) This Type Examination Certificate relates only to the design, examination and tests of the specified product in accordance to the standard list. Further requirements of the Directive apply to the manufacturing process and supply of this personal protective equipment. These are not covered by this certificate.
- (10) This Type Test Certificate is valid until 2028-03-19.

DEKRA Testing and Certification GmbH
Bochum, 2023-03-20

signed: Krökel

Managing director

We confirm the correctness of the translation from the German original.
In the case of arbitration only the German wording shall be valid and binding.



Managing director

TRANSLATION

- (11) Appendix to
- (12) **Type Examination Certificate**
ZP/B031/23
- (13) 13.1 Subject and Type
Fixed installed stepped ladder
Type: ABS Treppenleiter

13.2 Description

The fixed installed stepped ladder of type ABS Treppenleiter is used to reach workplaces at higher positions; it consists of aluminium profiles and aluminium grids. The handrail is made of aluminium tubes of \varnothing 30 mm and it is used to collectively protect people against falls from a height (Fig. 1).

The stepped ladder is mounted to surfaces of sufficient bearing strength. The platform height that is maximum possible is 3000 mm, and up to twelve steps are possible. The product specification describes the dimensioning of the product and is provided in Table 1.



Fig. 1: ABS Treppenleiter

Table 1: Product specification with product dimensioning

Detail	ABS Treppenleiter
Number of steps	12
Max. platform height	3000 mm
Max. platform size	600 x 1000 mm

- (14) Report

PB 23-014 dd. 2023-03-20